

AUTOMOTIVE GEAR SHIFT CABLE COMMODITIES



Construction	Liner ID (mm)	Steel wires diameter (mm)	Outside dia. OD (mm)	Liner material	Covering material
1+24-9,5	3,5	8,0	9,5	PTFE	PA6

Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Outside dia. OD (mm)	Flat wire material	Covering material
12+6+1	2,5	2,5x0,4	3,20	SS Aisi 430	-
12+1	2,5	2,5x0,4	3,20	SS Aisi 430	-

12+6+1	2,5	2,5x0,3	3,30	Bright high carbon steel	PA6
12+1	2,5	2,5x0,3	3,30		PA6

TRUCK GEAR SHIFT CABLE COMMODITIES



Construction	Liner ID (mm)	Steel wires diameter (mm)	Outside dia. OD (mm)	Liner material	Covering material
1+29-10,3	5,0	8,4	10,3	HDPE/POM	PA6-TPEE

Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Outside dia. OD (mm)	Flat wire material	Covering material
12+6+1	4,0	2,5x0,45	4,7	SS Aisi 430	-
18+17+1	4,0	2,5x0,4	4,65	SS Aisi 304	-
12+1	2,5	2,5x0,4	(3,2) 4,7	SS Aisi 430	PA6


BINDER WIRE CONDUITS & FLAT WIRE ROPES



Construction	Liner ID (mm)	Steel wires diameter (mm)	Outside dia. OD (mm)	Liner material	Covering material
1+17-8,7 VLD	3,1	7,4	8,7	HDPE	LDPE
1+16-13,4 LD	3,8	7,7	13,4	HDPE	LDPE
1+21-15,2 MD	5,2	9,5	15,2	HDPE	LDPE
1+26-17,3 HD	6,7	11,6	17,3	HDPE	LDPE

Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Outside dia. OD (mm)	Flat wire material	Covering material
12+6+1	2,0	2,3x0,45	2,7	SS Aisi 430	-
12+6+1	2,5	2,3x0,50	3,35	SS Aisi 430	-
12+6+1	4,0	2,5x0,4	4,6	SS Aisi 430	-
12+6+1	5,3	2,5x0,4	6,0	SS Aisi 430	-


GENERAL PURPOSE CONTROL CABLE COMMODITIES



Construction	Liner ID (mm)	Steel wires diameter (mm)	Outside dia. OD (mm)	Liner material	Covering material
1+19-6,9/8,3	2,3	5,6	6,9-8,3	HDPE	HDPE
1+19-9,5	3,6	7,1	9,5	HDPE	HDPE
1+29-10	4,1	8,5	10,0	HDPE	HDPE
1+24-11,5	5,1	8,9	11,5	HDPE	HDPE
1+23-13,0	6,2	10,5	13,0	HDPE	HDPE

Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Outside dia. OD (mm)	Flat wire material	Covering material
9,1	1,6	2x0,25	2,0	SS Aisi 304	-
12+6+1	2,5	2,3x0,45	3,2	SS Aisi 430	-
12+1	3,0	-	3,7	-	PA6
12+6+1	4,0	2,5x0,45	4,7	SS Aisi 430	-
12+6+1	5,0	2,5x0,4	5,65	SS Aisi 430	-

SUN ROOF & WINDOWS LIFTER DRIVE CABLE COMMODITIES



Flexible shaft construction	Shaft diameter (mm)	Helix cable diameter (mm)	Outside diameter OD (mm)	Flocked Yarn
1+6+6+6	2,4	0,8	3,81	-
1+6+6	2,7	1,0	4,7	PA6.6
1+6+6+6	3,75	1,6	6,55	PA6.6