

AUTOMOTIVE GEAR SHIFT CABLE COMMODITIES



Outside dia. D (mm)	Construction	Liner D (mm)	Steel wires dia. (mm)	Liner material	Covering material
9,5	1+24-9,5	3,5	8,0	PTFE	PA6

Outside dia. D (mm)	Rope construction	Rope dia. (mm)	Flat wire dim. (mm)	Flat wire material	Covering material
3,20	12+6+1	2,5	2,5x0,4	SS Aisi 430	-
3,20	12+1	2,5	2,5x0,4	SS Aisi 430	-
3,30	12+6+1	2,5	2,5x0,3	Bright high carbon steel	PA6
3,30	12+1	2,5	2,5x0,3		PA6

TRUCK GEAR SHIFT CABLE COMMODITIES



Outside dia. D (mm)	Construction	Liner ID (mm)	Steel wires dia D2 (mm)	Liner material	Covering material
10,3	1+29-10,3	5,0	8,4	HDPE/POM	PA6-TPEE

Outside dia. D (mm)	Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Flat wire material	Covering material
4,7	12+6+1	4,0	2,5x0,45	SS Aisi 430	-
4,65	18+17+1	4,0	2,5x0,4	SS Aisi 304	-
(3,2) 4,7	12+1	2,5	2,5x0,4	SS Aisi 430	PA6

BINDER WIRE CONDUITS & FLAT WIRE ROPES



Outside dia. D (mm)	Construction	Liner D1 (mm)	Steel wires dia. (mm)	Liner material	Covering material
8,7	1+17-8,7 VLD	3,1	7,4	HDPE	LDPE
13,4	1+16-13,4 LD	3,8	7,7	HDPE	LDPE
15,2	1+21-15,2 MD	5,2	9,5	HDPE	LDPE
17,3	1+26-17,3 HD	6,7	11,6	HDPE	LDPE

Outside dia. D (mm)	Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Flat wire material	Covering material
2,7	12+6+1	2,0	2,3x0,45	SS Aisi 430	-
3,35	12+6+1	2,5	2,3x0,50	SS Aisi 430	-
4,6	12+6+1	4,0	2,5x0,4	SS Aisi 430	-
6,0	12+6+1	5,3	2,5x0,4	SS Aisi 430	-


GENERAL PURPOSE CONTROL CABLE COMMODITIES



Outside dia. D (mm)	Construction	Liner D1 (mm)	Steel wires diameter (mm)	Liner material	Covering material
6,9-8,3	1+19-6,9/8,3	2,3	5,6	HDPE	HDPE
9,5	1+19-9,5	3,6	7,1	HDPE	HDPE
10,0	1+29-10	4,1	8,5	HDPE	HDPE
11,5	1+24-11,5	5,1	8,9	HDPE	HDPE
13,0	1+23-13,0	6,2	10,5	HDPE	HDPE

Outside dia. D (mm)	Rope construction	Rope diameter (mm)	Flat wire dim. (mm)	Flat wire material	Covering material
2,0	9,1	1,6	2x0,25	SS Aisi 304	-
3,2	12+6+1	2,5	2,3x0,45	SS Aisi 430	-
4,7	12+6+1	4,0	2,5x0,45	SS Aisi 430	-
5,65	12+6+1	5,0	2,5x0,4	SS Aisi 430	-

SUN ROOF & WINDOWS LIFTER DRIVE CABLE COMMODITIES



Outside dia. D2 (mm)	Pitch p (mm)	Flexible shaf construction	Shaft diameter D1 (mm)	Helix cable diameter d (mm)	Flocked Yarn
3	1,67	1+9	1,6	0,8	-
3,81	-	1+6+6+6	2,4	0,8	-
4,7	2,54	1+6+6	2,7	1,0	PA6.6
6,55	-	1+6+6+6	3,75	1,6	PA6.6
7,9	4,23	1+9+9+18	4,36	1,93	-